# 268


### MADE IN USA.

2-way sound systems

268 products have extraordinary dynamic response, especially in the low-frequency performance, the outbreak of the dynamic completely, so that you could imagine.

Mini-box design, but also reflects the professional level CSP professional audio products.

2-way sound systems, special Flying Version. The 268 loudspeaker yields 90 degrees horizontal coverage at 90 degrees vertical.



## **Specifications**:

System Type: 2-way, Full range, bass ported LF (1 x Csp 12LV2x)

Frequency Range: 60 Hz - 20 kHz (-10 dB) 80 Hz - 20 kHz (+/-3 dB)

Power Capacity: 300 W Continuous 1200 W Peak

-50

Recommended Power Amplifier: PaulAudio 202

Sensitivity (1w/1m): 98 dB

Maximum Output: 128.8 dB

Nominal Impedance: 8 Ohms

Nominal Dispersion: 90° x 90°

Crossover: T5r268

Drivers: HF (1 x Csp H452)

High Frequency Driver Protection: none

Input Connection: One two-terminal barrier strip input connectors

Enclosure Hardware: 3/4" MDF wood, UPWEJ Special black polyurea finish

Grille: 18 gauge perforated steel, additional powder coated

Dimensions (H x W x D): 19.375" x 14.375" x 13.75" 432 mm x 365 mm x 349 mm

Weight: 37 lbs (16 kg)

Shipping weight: 40 lbs (18 kg)



#### **APPLICATIONS:**

Sound Reinforcement Clubs, Karaoke Clubs, Health Clubs Offices, Classrooms, Meeting Rooms A/V Systems Houses of Worship Sport Facilities Distributed Systems

### **FEATURES:**

Lv2 Technology, Flying version High power handling - 300 watts(average) and 1200 watts(peak) power capacity

90° x 90° horn designed for even coverage and smooth response on and off axis

1" Titanium HF Driver

The advanced network topology crossover design shapes the frequency response to deliver coherent summation in the crossover region

3/4" MDF wood, UPWEJ Special(Ultrachrome Protecting wood enclosures) black polyurea finish

18 gauge perforated steel, additional powder coated Manufactured with Pride in the United States

Csp Professional 5157 Cliffwood Dr., Montclair, CA 91763 USA info@csppro.com All information is Copyright © 2005 Csp

www.csppro.com