2-way sound systems

100% Factory Quality Control


100% Factory Speaker Construction

100% Factory Tested

5 year Warranty

Manufactured with Pride in the United States

290 is composed of 8" units. Ultra heavy low frequency, bright mid to high frequency with high sensitivity and large output. It is a fusion of high-end acoustics and professional output power. 2-way sound systems, special Flying Version.





## **SPECIFICATIONS:**

System Type: Drivers:

2-way, Full range, bass ported

HF (1 x Csp H452)

Frequency Range:

50 Hz - 20 kHz (-10 dB)

65 Hz - 20 kHz (+/-3 dB)

Power Capacity:

250 W Continuous

1000 W Peak

Recommended Power

Amplifier:

PaulAudio 202

Sensitivity (1w/1m):

97 dB

Maximum Output:

127 dB

Nominal Impedance:

8 Ohms

Nominal Dispersion:

90° x 90°

Crossover: T5r290

 $LF (1 \times Csp \ 8LV2x)$ 

Input Connection:

One two-terminal barrier strip

input connectors

Enclosure Hardware:

3/4" MDF wood, UPWEJ black

polyurea finish

Grille:

18 gauge perforated steel, additional powder coated

Dimensions (H x W x D):

10.875" x 16" x 10.875"

276 mm x 406 mm x 276 mm

Weight:

28.5 lbs (12.7 kg)

Shipping weight:

60.5 lbs (27 kg)/2Pcs

## APPLICATIONS:

Clubs, Karaoke Clubs, Health Clubs Offices, Classrooms, Meeting Rooms

A/V Systems

Houses of Worship

Sport Facilities

Distributed Systems

## **FEATURES:**

Lv2 Technology, Flying version

High power handling - 250 watts(average) and 1000

watts(peak) power capacity

90° x 90° horn designed for even coverage and smooth

response on and off axis

1" Titanium HF Driver

The advanced network topology crossover design shapes the frequency response to deliver coherent summation in the crossover region

3/4" MDF wood, UPWEJ (Ultrachrome Protecting wood

enclosures) black polyurea finish

18 gauge perforated steel, additional powder coated

Csp Professional 5157 Cliffwood Dr., Montclair, CA 91763 USA info@csppro.com All information is Copyright © 2005 Csp

www.csppro.com