

CLX915

MADE IN USA.

2-way sound systems

Different music must be played using different method. That is why Csp offers so many series of products. It is appropriate to say that the CLS series is designed for live performance.

Live musical performance has special requirements for sound restoration. For example, we first consider flexibility for low frequency. (We also take strength into consideration but not much.) What mid to high frequency requires is penetration, not smoothness and fineness. Whether low frequency, mid or high frequency, they all require sufficient large receiving power capability. These are what CLX possess.

Full-range two-way systems feature woofer cone geometry and special cone materials, to lower distortion and smooth response in the upper woofer octaves.

This allows a crossover frequency high enough 1800 Hz to utilize, without compromising maximum acoustic output, a compression driver with a 1.75" diameter diaphragm.

1 x 15" Lv3 technology woofer

1 x H450 compression driver



SPECIFICATIONS:

System Type: 2-way, Full range, bass ported	Drivers: LF (1 x Csp 15LV3) HF (1 x Csp H450)
Frequency Range: 50 Hz - 18 kHz (-10 dB) 60 Hz - 18 kHz (+/-3 dB)	High Frequency Driver Protection: SP DDPJ
Power Capacity: 600 W Continuous 2400 W Peak	Input Connection: One Neutrik NL4, Dual 1/4" phone jacks in parallel
Recommended Power Amplifier: P.PA Series	Enclosure Hardware: 3/4" MDF wood, UPWEJ black polyurea finish
Sensitivity (1w/1m): 101 dB	Grille: 18 gauge perforated steel, additional powder coated
Maximum Output: 135 dB	Dimensions (H x W x D): 29.875" x 16.875" x 19.875" 760 mm x 430 mm x 500 mm
Nominal Impedance: 8 Ohms	Weight: 80 lbs (36 kg)
Nominal Dispersion: 90° x 40°	Shipping weight: 89 lbs (40 kg)
Crossover : T5	

APPLICATIONS:

Concerts
Clubs
Mobile DJ
Houses of Worship
Live performance stage monitoring
Entertainment

FEATURES:

LV3 Technology
Trapezoid Design
Die-cast aluminum basket
Full-range passive operation or Bi-amplified (optional)
SPDDP™ (Speaker Distortion Dynamic Protection)
UPWE™ (Ultrachrome Protecting wood enclosures) black polyurea finish
Neutrik Speakon & Dual 1/4 Phone Jacks in Parallel
Manufactured with Pride in the United States
pole mount socket
Flying version, the CLX915F is available

Csp Professional
5157 Cliffwood Dr., Montclair, CA 91763 USA
info@csppro.com
All information is Copyright © 2005 Csp