

# CLX925

MADE IN USA.

## 2-way sound systems

Different music must be played using different method. That is why Csp offers so many series of products. It is appropriate to say that the CLS series is designed for live performance.

Live musical performance has special requirements for sound restoration. For example, we first consider flexibility for low frequency. (We also take strength into consideration but not much.) What mid to high frequency requires is penetration, not smoothness and fineness. Whether low frequency, mid or high frequency, they all require sufficient large receiving power capability. These are what CLX possess.

220H horn and two 15" 15LV3 woofers with 3" high temperature voice coils, the CLX925 is an 4-ohm, 2-way passive bass reflex design. Providing the flexibility to be used stand-alone, arrayed, or in conjunction with the CLX928B subwoofer, the CLX925 is rated at 1200 watts Continuous with a frequency response of 40Hz to 18kHz.

2 x 15" LV3 technology woofer

1 x H450 compression driver



## SPECIFICATIONS:

System Type: 2-way, Full range, bass ported	Drivers: LF (2 x Csp 15LV3) HF (1 x Csp H450)
Frequency Range: 40 Hz - 18 kHz (-10 dB) 55 Hz - 18 kHz (+/-3 dB)	High Frequency Driver Protection: SP DDPJ
Power Capacity: 1200 W Continuous 4800 W Peak	Input Connection: One Neutrik NL4, Dual 1/4" phone jacks in parallel
Recommended Power Amplifier: P.PA Series	Enclosure Hardware: 3/4" MDF wood, UPWEJ black polyurea finish
Sensitivity (1w/1m): 103 dB	Grille: 18 gauge perforated steel, additional powder coated
Maximum Output: 140 dB	Dimensions (H x W x D): 45.375" x 19.875" x 20.375" 1150 mm x 500 mm x 517 mm
Nominal Impedance: 4 Ohms	Weight: 131 lbs (58 kg)
Nominal Dispersion: 60° x 40°	Shipping weight: 140 lbs (62 kg)
Crossover : T6x1	

### APPLICATIONS:

Sound Reinforcement  
Clubs, Karaoke Clubs, Health Clubs  
Offices, Classrooms, Meeting Rooms  
A/V Systems  
Houses of Worship  
Sport Facilities  
Distributed Systems

### FEATURES:

LV3 Technology  
Trapezoid Design  
Dual 15" woofer, Die-cast aluminum basket  
Full-range passive operation or Bi-amplified (optional)  
SP DDP™ (Speaker Distortion Dynamic Protection)  
UPWE™ (Ultrachrome Protecting wood enclosures) black  
polyurea finish  
Neutrik Speakon & Dual 1/4 Phone Jacks in Parallel  
Manufactured with Pride in the United States

Csp Professional  
5157 Cliffwood Dr., Montclair, CA 91763 USA  
info@cspopro.com  
All information is Copyright © 2005 Csp