2-way sound systems http://csppro.com/p/k10.asp

100% Factory Quality Control


100% Factory Speaker Construction

100% Factory Tested

5 year Warranty

Manufactured with Pride in the United States

The K10 loudspeaker yields 90 degrees horizontal coverage at 90 degrees vertical





Specifications:

System Type: Drivers:

2-way, Full range, bass ported LF (2 x Csp 8LV2x)

HF (1 x Csp H450)

Frequency Range:

45 Hz - 20 kHz (-10 dB) High Frequency Driver

55 Hz - 20 kHz (+/-3 dB) Protection:

SP DDPTM

Power Capacity:

400 W Average Input Connection:

1600 W Peak Neutrik Speakon in Parallel

Recommended Power

Amplifier:

Csp.ms 217

3/4" MDF wood, UPWE™ Special black polyurea finish

Enclosure Hardware:

Sensitivity (1w/1m):

98 dB

18 gauge perforated steel,

additional powder coated

Maximum Output:

130 dB

Dimensions (H x W x D):

9.625" x 23.5" x 12"

Nominal Impedance:

245 mm x 600 mm x 305 mm

4 Ohms

Weight:

Nominal Dispersion:

36 lbs (16 kg)

90° x 90°

Shipping weight:

Crossover: T5rK10

40.5 lbs (18 kg)

APPLICATIONS:

Sound Reinforcement

Clubs, Karaoke Clubs, Health Clubs

Offices, Classrooms, Meeting Rooms

A/V Systems

Houses of Worship

Sport Facilities

Distributed Systems

FEATURES:

Damping Speaker Technology

High power handling - 400 watts(average) and 1600

watts(peak) power capacity

90° x 90° horn designed for even coverage and smooth

response on and off axis

1" Titanium HF Driver

SP DDP™ Distortion Dynamic Protection

The advanced network topology crossover design shapes the frequency response to deliver coherent summation in the

crossover region

3/4" MDF wood, UPWETM Special(Ultrachrome Protecting

wood enclosures) black polyurea finish

18 gauge perforated steel, additional powder coated

Manufactured with Pride in the United States

Csp Professional

5157 Cliffwood Dr., Montclair, CA 91763 USA

info@csppro.com

All information is Copyright © 2005 Csp

www.csppro.com