
K3

Made IN USA. 3-way sound systems http://csppro.com/p/k3.asp

Tradition has become tradition, must have his reasons. K3 traditional concept of professional audio, only a simple box structure changes You will be able to meet the most stringent of professional sound picky.

If you can not judge what is the professional audio, K3 will give you the full answer, the true meaning of the U.S. professional audio.





Specifications:

System Type: 3-way, Full range, bass ported

Frequency Range: 45 Hz - 20 kHz (-10 dB) 55 Hz - 20 kHz (+/-3 dB)

Power Capacity: 600 W Average 2400 W Peak

Recommended Power Amplifier: P.PA Series

Sensitivity (1w/1m): 103 dB

Maximum Output: 136.8 dB

Nominal Impedance: 4 Ohms

Nominal Dispersion: $90^{\circ} \times 50^{\circ}$

Crossover: T5rK1 Drivers: LF (2 x Csp 15LV2i) HF (1 x Csp H450; 1 x PZT)

High Frequency Driver Protection: SP DDPJ

Input Connection: Neutrik Speakon in Parallel

Enclosure Hardware: 3/4" MDF wood, UPWEJ Special black polyurea finish

Grille: 18 gauge perforated steel, additional powder coated

Dimensions (H x W x D): 33.25" x 26.25" x 18" 845 mm x 667 mm x 457 mm

Weight: 108 lbs (48 kg)

Shipping weight: 112 lbs (50 kg)



APPLICATIONS:

Sound Reinforcement Clubs, Karaoke Clubs, Health Clubs Offices, Classrooms, Meeting Rooms A/V Systems Houses of Worship Sport Facilities Distributed Systems

FEATURES:

Lv2 Technology

High power handling - 600 watts(average) and 2400 watts(peak) power capacity

 90° x 50° horn designed for even coverage and smooth response on and off axis

1" Titanium HF Driver

SP DDPJ Distortion Dynamic Protection

The advanced network topology crossover design shapes the frequency response to deliver coherent summation in the crossover region

3/4" MDF wood, UPWEJ Special(Ultrachrome Protecting wood enclosures) black polyurea finish

18 gauge perforated steel, additional powder coated Manufactured with Pride in the United States

Csp Professional 5157 Cliffwood Dr., Montclair, CA 91763 USA info@csppro.com All information is Copyright © 2005 Csp

www.csppro.com