


P.PA4-LV

MADE IN USA.

15" Direct-Radiating Bass-Reflex Subwoofer

The P.PA-LV Series are built exclusively in Csp's own USA manufacturing facility, with internal components selected for premium quality and proven durability. Each modular subassembly is pre-tested, and the assembled P.PA Series receives a rigorous hot room burn-in before thorough final checkout on precision test equipment.

Built-in P.PA amplifier module designed provides 6000 Watts continuous Power with in 4Ohms bridged.



SPECIFICATIONS:

System Type: Direct-Radiating Bass-Reflex Subwoofer	LF (1 x Csp 15LV3) High Frequency Driver Protection: none
Frequency Range: 35 Hz - 2 kHz (-10 dB) 50 Hz - 1.8 kHz (+/-3 dB)	Input Connection: One two-terminal barrier strip input connectors
Power Capacity: 500 W Continuous 2000 W Peak	Enclosure Hardware: 3/4" MDF wood, UPWE™ Special black polyurea finish
Built-in Amplifier: P.PA4	Grille: 18 gauge perforated steel, additional powder coated
Sensitivity (1w/1m): 97 dB	Dimensions (H x W x D): 27" x 18.5" x 20" 680 mm x 470 mm x 500 mm
Maximum Output: 130 dB	Weight: 139 lbs (62 kg)
Nominal Impedance: 8 Ohms	Shipping weight: 148 lbs (66 kg)
Nominal Dispersion: None	
Crossover: T5r255	
Drivers:	

APPLICATIONS:

Sound Reinforcement
Clubs, Karaoke Clubs, Health Clubs
Offices, Classrooms, Meeting Rooms
A/V Systems
Houses of Worship
Sport Facilities
Distributed Systems

FEATURES:

Lv3 Technology
High power handling - 500 watts(average) and 2000 watts(peak) power capacity
3/4" MDF wood, UPWE™ Special(Ultrachrome Protecting wood enclosures) black polyurea finish
18 gauge perforated steel, additional powder coated
Manufactured with Pride in the United States

Csp Professional
5157 Cliffwood Dr., Montclair, CA 91763 USA
info@cspopro.com
All information is Copyright © 2005 Csp

www.cspopro.com

P.PA4-LV

Csp